



# SKYWING Flood Light SWTFL Series



## Introduction

- SKYWING Floodlight has been designed to deliver high lumen output and save energy cost for customers who are constantly looking for ways to reduce the amount of energy required to light their facilities. It's compact and elegant design makes it suitable for other general lighting applications not only outdoor lighting but also indoor lighting.
- Application: Warehouse, Factory, Airport, Manufacturing plant, Car Showroom etc.

## Technical Specifications

Art.-Nr.	Part.-Nr.	Power (W)	Lumen (lm)	Efficacy (lm/W)	Angle (°)	CCT (K)	CRI (Ra)	Weight (Kg)	IP	Dimming
00040001	SWTFL048-110VC0	48	6240	130	110	5000	≥80	4.9	66	N/A
00040002	SWTFL048-060VC0	48	5760	120	060	5000	≥80	4.9	66	N/A

\*\* The specification may be subject to change without prior notice.

(Tolerance: ±5%)

Voltage: AC100-220V

Power: 48W

Power Factor: >0.9

Beam angle: 110° / 60°

CCT: Standard 5000K(4000K optional)

LED Package: Samsung

LED SMPS: Own development

Working temp: -30°C ~ 60°C

Storage temp: -30°C ~ 80°C

Lifespan: 50,000hrs

Material: Die-cast aluminum Housing  
Tempered glass cover

Color: Silver Grey

## Dimension & Polar Distribution

